

Specifications

- 2" door sections are formed from 27-gauge exterior galvanized draw quality steel
- Section joints are roll-formed into a tongue-and-groove design which produces a superior weather seal
- 1-13/16" CFC⁴ free polystyrene insulation, glued on both sides
- Extra heavy paint system¹ available in white, almond or sandstone
- Accents wood tones available in cedar, mahogany, dark oak and light oak
- Bottom weather seal utilizes an aluminum retainer and extruded virgin vinyl
- Concealed steel plates run continuously from top to bottom of each section for fastening hardware
- R-value⁵: 9.65

Color Selections³



accents

WINDOW & GLASS OPTIONS

Add a touch of elegance and complement the outside of your home with the addition of decorative and designer glass options. These options are an investment designed to improve the natural beauty of the exterior while adding to the value of your home.

Window Design Trims



Cascade



Stockton



2-2 Piece Arched Stockton




3 Piece Arched Stockton



4 Piece Arched Stockton



Madison



2-2 Piece ArcheMadison




3 Piece Arched Madison




4 Piece Arched Madison

Designer Lites²



Plain DSB




Tinted



Obscure



Glue Chip




Newport



Hampton



Florence



LaSalle


External Hardware



Spade




Wrought Iron



Barcelona
Handles/Hinges



Barcelona
Pull-Rings/Angle Brackets



PANEL CONSTRUCTION

These models utilize a 1-13/16" CFC⁴ free polystyrene insulation glued on both sides between 27-ga. exterior and 27-ga. interior skins. The front and back skins are locked together in a tongue and groove design for years of worry free protection.

Footnotes

1. Extra heavy paint system consists of .25 mil. primer with rust inhibitor and a .75 mil. coating of baked-on polyester paint. 2. All designer lights are either transparent or semi-transparent. For all available window options, please see our Glass Option Brochure. 3. Refer to samples at your local garage door professional for exact color match. 4. Chlorofluorocarbon (CFC) free. 5. R-value testing is in accordance with ASTM C518 standards.

All information presented is based on the specifications and features available at the time of printing and is subject to change without notice.

